

INDEXPage1- SAUNA ROOM LAYOUTS2792- SAUNA HEATERS2833- SAUNA ACCESSORIES2844- STEAM ACCESSORIES2855- STEAM ROOM LAYOUTS6-2866- STEAM GENERATOR287






Sauna & Steam Rooms





Box Type Sauna



Corner Sauna





Outdoor Sauna

Standard sauna rooms come in different shapes and sizes, from 2 persons up to 11 persons capacity, with over 30 different designs to choose from. Most common saunas are indoor sauna rooms. Indoor sauna rooms are more private.


It is more convenient to position the sauna near the bathroom or Jacuzzi because as a rule, sauna requires a shower or a bath before using it.

- There are four different standard designs available:
- BOX TYPE SAUNA ROOM: It is ideal for easy installation on any given space along with its traditional box type appearance and cozy interior.
- CORNER SAUNA ROOMS: Designed to ingeniously fit in on corners of the premises without sacrificing convenience. It reduces the needed doorway space.
- OUTDOOR SAUNA ROOMS: An exquisite scenery to a very satisfying sauna bath. Best placed near swimming pools or bathing facilities. It stands strong to resist nature's harsh elements with its high enduring asphalt roof and beautiful lacquered spruce walls.
- CUSTOMIZED SAUNA ROOMS: With our expertise in building saunas, we can provide a Customized Sauna Design that meets your expectations. Shape and size of area is limitless as long as a proper ventilation and drainage system of the allotted area complies with the standards of sauna. Sauna rooms will be built according to your specifications.


Customized Sauna




1- SAUNA ROOM LAYOUTS:




CODE: S-219RS




CODE: S-515RL 1540




CODE: S-519MS






CODE: S-219LS



CODE: S-515LL




CODE: S-919MS




CODE	NO. OF PERSONS	OUTER DIMENSION	HEATER
		mm	kw
S-212RS	2	1195x1195x2020	3.0
S-212LS	2	1195x1195x2020	3.0
S-215RS	3	1195x1540x2020	3.6
S-215LS	3	1195x1540x2020	3.6
S-219RS	4	1195x1885x2020	3.6
S-219LS	4	1195x1885x2020	3.6
S-515RS	3	1540x1540x2020	4.5
S-515LS	3	1540x1540x2020	4.5

* Sauna heater not included.


* Sauna accessories not included.








CODE: S-519RL




CODE: S-919RL











CODE: S-519LL



CODE: S-919LL 1885



CODE NO. OF PERSONS OUTER DIMENSION

MENSION HEATER


		mm	kw
S-515RL	4	1540x1540x2020	4.5
S-515LL	4	1540x1540x2020	4.5
S-519RL	5	1540x1885x2020	6.0
S-519LL	5	1540x1885x2020	6.0
S-519MS	4	1540x1885x2020	6.0
S-919MS	4	1885x1885x2020	4.5
S-919RL	6	1885x1885x2020	6.0
S-919LL	6	1885x1885x2020	6.0




CODE:S-919MD 1885




CODE:S-922LS




CODE:S-929MD






2230


CODE:S-922RL



CODE:S-222LL



CODE:S-229MD



CODE NO. OF PERSONS OUTER DIMENSION HEATER

		mm	kw
S-919MD	6	1885x1885x2020	6.0
S-922RL	7	1885x2230x2020	8.0
S-922LL	7	1885x2230x2020	8.0
S-922RS	5	1885x2230x2020	8.0
S-922LS	5	1885x2230x2020	6.0
S-926MS	6	1885x2575x2020	8.0
S-926MIL	8	1885x2575x2020	8.0
S-926MRL	8	1885x2575x2020	8.0

2575

CODE:S-226MIL


CODE:S-922LL

CODE:S-926MIL


1885


1885

2230



CODE:S-229RL





CODE:S-922RS

CODE:S-926MRL

CODE:S-226MRL

1885

885

2230

2230

2575

2575

7



CODE NO. OF PERSONS OUTER DIMENSION HEATER


		mm	kw
S-222RL	8	2230x2230x2020	8.0
S-222LL	8	2230x2230x2020	8.0
S-226MIL	9	2230x2575x2020	9.0
S-226MRL	9	2230x2575x2020	9.0
S-929MD	8	1885x2920x2170	9.0
S-229MD	12	2230x2920x2170	9.0
S-229RL	11	2230x2920x2170	9.0
S-229LL	11	2230x2920x2170	9.0

* Sauna heater not included.

* Sauna accessories not included.





1540







CODE:S-519RSC












CODE:S-519LSC







CODE	NO. OF PERSONS	OUTER DIMENSION	HEATER
		mm	kw
S-212RSC	2	1195x1195x2020	3.0
S-212LSC	2	1195x1195x2020	3.0
S-215RSC	3	1195x1540x2020	3.6
S-215LSC	3	1195x1540x2020	3.6
S-515RAC	2 4	1540x1540x2020	3.6
S-515LAC	4	1540x1540x2020	3.6
S-515RSC	3	1540x1540x2020	4.5
S-515LSC	3	1540x1540x2020	4.5

* Sauna heater not included.


* Sauna accessories not included.



CODE:S-515RSC



CODE:S-519RLC









1195

CODE:S-215LSC



CODE:S-519LLC




CODE:S-919LLC 1885


CODE	NO. OF PERSONS	OUTER DIMENSION	HEATER
		mm	kw
S-519RSC	4	1540x1885x2020	6.0
S-519LSC	4	1540x1885x2020	6.0
S-519RLC	5	1540x1885x2020	6.0
S-519LLC	5	1540x1885x2020	4.5
S-919RSC	4	1885x1885x2020	6.0
S-919LSC	4	1885x1885x2020	6.0
S-919RLC	6	1885x1885x2020	6.0
S-919LLC	6	1885x1885x2020	6.0




CODE:S-922RSC 2230 1885









CODE:S-929RLC





CODE:S-929LLC



CODE NO. OF PERSONS OUTER DIMENSION HEATER kw mm S-922RSC 5 1885x2230x2020 8.0 5 8.0 S-922LSC 1885x2230x2020 S-922RLC 7 1885x2230x2020 8.0 7 S-922LLC 1885x2230x2020 8.0 S-926RLC 8 1885x2575x2020 8.0 S-926LLC 8 1885x2575x2020 8.0 6 S-926RSC 1885x2575x2020 8.0 8.0 S-926LSC 6 1885x2575x2020

* Sauna heater not included.


* Sauna accessories not included.


CODE:S-922LSC



CODE:S-926LLC 2575 1885







CODE:S-926RSC




1885

2230


CODE:S-926LSC

CODE:S-226LLC


S-922LLC




2575



CODE:S-229RLC



CODE:S-229LLC



CODE	NO. OF PERSONS	OUTER DIMENSION	HEATER
		mm	kw
S-222RLC	8	2230x2230x2020	8.0
S-222LLC	8	2230x2230x2020	8.0
S-226RLC	9	2230x2575x2020	9.0
S-226LLC	9	2230x2575x2020	9.0
S-929RLC	10	1885x2920x2170	9.0
S-929LLC	10	1885x2920x2170	9.0
S-229RLC	11	2230x2920x2170	9.0
S-229LLC	11	2230x2920x2170	9.0

CODE:S-226RLC 2575

2230



2- SAUNA HEATERS

"NORDIA" SAUNA HEATER

- Nordia Sauna Heater with intelligent digital controller.
- Two sets of independent contacts for the thermostatic control and the thermal cut out.
- Temperature setting 50-110°C or 122-230°F.
- Intelligent Sequential heating system, Double over heat protection system for both sauna room and sauna heater.
- Setting time from 0-12 hours.
- Working time: 30 minutes to 12 hours.
- LED diagnostic system.
- Available in 3kW, 4kW,4.5kW, 6kW, 8kW and 9kW.



Intelligent Digital Controler

CODE	POWER	SAUNA ROO m		CURF A		DIMENSIONS	PACKING	WEIGHT	VOLUME
	kW	MIN	MAX	230V 1N~	400V 3N~	mm		kg	m³
ND3	3.0	2	4	13		425 x 320 x 615	1	11	0.09
ND4	4.0	3	5	17		425 x 320 x 615	1	12	0.09
ND4.5	4.5	4	6	19.5	6.5	425 x 320 x 615	1	13	0.09
ND6	6.0	5	8	27	9	425 x 320 x 615	1	14	0.09
ND8	8.0	7	11	35	12	425 x 320 x 615	1	15	0.09
ND9	9.0	8	12	39	13	425 x 320 x 615	1	16	0.09


"ZELMA" SAUNA HEATER

- Zelma heavy duty Sauna Heater with stainless steel jacket, intelligent controller and separate control box.
- Two sets of independent contacts for the thermostatic control and the thermal cut out.
- Temperature setting 50-110°C or 122-230°F.
- Intelligent Sequential heating system, double over heat protection system for both sauna room and sauna heater.
- LED diagnostic system, comply with the new CE standard.
- Available in 9KW, 10.5KW,12kW, 14.1kW, 16.2kW, 18kW and 20.1kW.



CODE	POWER	SAUNA ROO m		CURF		DIMENSIONS	PACKING	WEIGHT	VOLUME
	kW	MIN	MAX	230V 1N~	400V 3N~	mm		kg	m³
ZL9	9	2	4	13		670 x 500 x 660	1	16	0.22
ZL10.5	10.5	3	5	17		670 x 500 x 660	1	17	0.22
ZL12	12	4	6	19.5	6.5	670 x 500 x 660	1	18	0.22
ZL14.1	14.1	5	8	27	9	670 x 500 x 660	1	19	0.22
ZL16.2	16.2	7	11	35	12	670 x 500 x 660	1	20	0.22
ZL18	18	8	12	39	13	725 x 565 x 675	1	21	0.22
ZL20.1	20.1					725 x 565 x 675	1	22	0.22





SAUNA ROOM ACCESSORIES KIT

A kit of sauna accessories is included with every purchase of sauna room, containing:

- 1- Light Cover
- 2-Light
- 3- Wooden pillow
- 4- Pail & Ladle
- 5- Sandtimer
- 6-Thermo-Hygrometer
- 7- An appropriate electric sauna heater.

Note: it is recommended to have 2 sauna lights in your sauna for a better ambiance.


3- SAUNA ACCESSORIES





S-132









S-158

S-141

Sauna & Steam Rooms



STEAM ROOMS


- Comprises seats full height glass door and its frame.
- Supplied complete with an intelligent steam generator having electronic control with digital display, inlet nozzle and auto drain down and self flushing function.
- Parts are constructed from extra strong fiberglass reinforced MPC to ensure an extended and trouble free service.
- Sizes can be custom made according to required dimensions, please refer to your AQUA dealer for further details.











4- STEAM ACCESSORIES





1.000			-			
	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
_	-	-	-	-	-	-
-	-	-	-	-	-	-
1-	-	-	-	-	-	-
- 1	-	-	-	-	-	-
-	_		100	-		


9	S-170 S-171			S-172
CODE	DESCRIPTION	PACKING	WEIGHT	VOLUME
			kg	m³
S-170	Steam Light	1	0.5	0.01
S-171	Hygrothermograph	1	0.5	0.01
S-172	Floor Mat 300x300mm	50	13	0.08
S-173	Thermostatic & Hydromassage Kit	1	0.5	0.01





5- STEAM ROOM LAYOUTS:

Sauna & Steam Rooms



CODE	NUMBER OF SEATING POSITIONS	OUTER DIMENSION cm	STEAM GENERATOR kw
S-2B	2	112x105x215	4
S-2B-L	2	130x120x215	4
S-5A	3	150x150x225	6
S-4B	4	190x130x225	6
S-6B	6	190x190x225	9
S-6D	5/6	212x134x225	9
S-8B	8	190x250x225	10.5

CODE	NUMBER OF SEATING POSITIONS	OUTER DIMENSION cm	STEAM GENERATOR kw
S-8D	7/8	212x194x225	10.5
S-10B	10	190x310x225	12
S-10D	9/10	212x254x225	12
S-12B	12	190x370x225	2x8
S-12D	11/12	212x314x225	2x8
S-14D	14	212x374x225	2x9

* Steam generator not included.

* Steam accessories not included.

286




5- STEAM GENERATOR:

- A new generation steam generator with a host of advanced features.
- An extra heavy duty and robust steam generator manufactured using top quality teflon coated incalloy elements that resist scaling combined with additional electronics for a long trouble free working life.
- All generators feature an advanced electronic control with on board diagnostics having a series of LEDs to show each operation of the boiler. The generator is fitted with several heating elements that operate sequentially, from cold both elements operate for rapid heating, when the steam room temperature is almost reached a number of the elements drops out, and the required temperature is achieved and maintained by the other elements alternating on and off to gently maintain the temperature without large fluctuations improving user comfort.
- All generators feature an auto drain down with a self flushing cycle to dump the boiler contents in a controlled manner - at the end of each steaming session the generator will stop for a few minutes to allow the water to cool a little then the drain valve will open and after a short time the cold water inlet valve will open to give a period of continuous flushing and draining. Flushing and draining the boiler reduces the buildup of damaging lime scale, cooling the elements before the final drainage helps prolong their useful life.
- Electronic controls with a digital display to enable temperatures of 30 to 60 degrees centigrade and time duration 15 to 240 minutes or continual operation with additional keys for a steam room light, keyboard lock, manual drain down etc.
- Steam inlet nozzle with facility for adding essential oils.
- Safety features include boil dry protection, thermal overload safety cut out and pressure relief valve.
- Complete with installation instructions, 12 months guarantee.
- Please note that for the commercial use of steam generators we strongly recommend the use of softened water, to reduce the buildup of lime scale and reduce maintenance, for additional fragrance injection please order an additional essence dosing kit.
- All steam generators comes with the steam inlet, on-demand steam button, intelligent digital controller & pressure relief valve.







CODE	POWER	VOLTAGE	PHASE	CURRENT			C		NSIONS Im	5			PACKING	WEIGHT	VOLUME
	kW	V	N~	А	А	В	С	D	Е	F	G	Н		kg	m³
SG-30	3.0	230	1	13	390	190	335	25	80	30	69	60	1	18	0.03
SG-40	4.0	230	1	17	390	190	335	25	80	30	69	60	1	19	0.03
SG-45	4.5	230/400	1/3	8.1	390	190	335	25	80	30	69	60	1	110	0.03
SG-60	6.0	230/400	1/3	10.8	390	190	335	25	80	30	69	60	1	111	0.03
SG-80	8.0	230/400	1/3	14	450	195	353	25	135	45	72	60	1	112	0.03
SG-90	9.0	230/400	1/3	16	450	195	353	25	135	45	72	60	1	113	0.03
SG-105	10.5	230/400	1/3	19	390	206	415	25	135	45	77	60	1	114	0.03
SG-120	12.0	230/400	1/3	21.8	390	260	415	25	135	45	77	60	1	115	0.03

