

TECHNICAL SPECIFICATIONS
DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL PVA PRIMER SEALER FOR MASONRY

DESCRIPTION	A special PVA based Primer Sealer with good sealing properties. It has excellent adhesion to cementitious surface. It contains antifungal & antibacterial additives.
RECOMMENDED USE	Primer Sealer for interior and exterior concrete, plaster, asbestos, brick work, etc.

TECHNICAL DATA

COLOURS	Clear
FINISH	Smooth
VOLUME SOLIDS	30 ± 2%
SPECIFIC GRAVITY KG/L	1.16 ± 0.05
THEORETICAL SPREADING RATE	15 - 10 M ² /LTR
RECOMMENDED (DFT) - MICRONS	20 - 30 per coat
RECOMMENDED (WFT) - MICRONS	65 - 100 per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 1
	Dry to recoat (hours) : 2 - 3

APPLICATION DATA

APPLICATION METHOD	Brush or Roller
THINNING (VOLUME)	10 - 15% depending on the surface.
THINNER / CLEANER	Water
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	Apply one coat of National PVA Primer Sealer for masonry on dry, clean surface. Then apply recommended system.

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.