

DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL STUCCO FILLER

DESCRIPTION	A PVA Copolymer based, homogenous smooth putty. It gives a smooth and levelled surface suitable for subsequent coats. It contains antifungal & antibacterial additives.
RECOMMENDED USE	Filler for interior concrete, plaster, masonry and wood works.

TECHNICAL DATA

COLOURS	White
FINISH	Smooth, Matt
VOLUME SOLIDS	60 ± 2%
SPECIFIC GRAVITY KG/L	1.68 ± 0.05
THEORETICAL SPREADING RATE	6 M ² /LTR
RECOMMENDED (DFT) - MICRONS	100 per coat
RECOMMENDED (WFT) - MICRONS	165 per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time. Touch dry (hours) : 1 - 2 Dry to recoat (hours) : 6 - 8

APPLICATION DATA

APPLICATION METHOD	Putty Knife
THINNING (VOLUME)	Ready for use
THINNER / CLEANER	Water
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	- National PVA Primer Sealer for Masonry (or) : 1 coat - National PVA Primer White : 1 coat - National Stucco Filler : 2 coats - Finally apply recommended system : 2 coats

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.