



TECHNICAL SPECIFICATIONS

DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL JOINT FILLER

DESCRIPTION	A polymer emulsion based special filler has been developed for gap filling up to 1 cm. It is based on flexible acrylic with inert filler. It contains antifungal and antibacterial additives.
RECOMMENDED USE	For gap filling of cementitious surface, wall, concrete, and suitable for instant application, ready to use for interior and exterior application.

TECHNICAL DATA

COLOURS	White
FINISH	Matt
APPEARANCE	Thick paste
SPECIFIC GRAVITY KG/L	1.35 ± 0.05
THEORETICAL SPREADING	Depends on the gap and surface
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affects the drying time Hard dry (hours) : 24

APPLICATION DATA

APPLICATION METHOD	Scraper, knife, blade
THINNING (VOLUME)	Ready to use.
THINNER / CLEANER	For cleaning water can be used.
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	Apply on clean, dust free surface National Joint Filler, to fill up the complete gap. If gap and cavity is more, then use polyurethane rope, before application of National Joint Filler.

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.