

DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL EGGSHELL EMULSION (MATT FINISH)

DESCRIPTION	A superfine quality, alkali resistant. Acrylic Copolymer based emulsion.
	It gives a matt eggshell decorative finish with excellent washability
	and good hiding power. It has excellent light and weather resistance. It
	contains antifungal and antibacterial additives.
RECOMMENDED USE	Decorative smooth finish for interior and exterior concrete, plaster,
	masonry, brick work, gypsum, asbestos and wood.

TECHNICAL DATA

COLOURS	As Per National Shade Card
FINISH	Matt
VOLUME SOLIDS	$40 \pm 2\%$
SPECIFIC GRAVITY KG/L	1.40 ± 0.05
THEORETICAL SPREADING RATE	10 - 8 M ² /LTR
RECOMMENDED (DFT) - MICRONS	40 - 50 per coat
RECOMMENDED (WFT) - MICRONS	100 - 125 per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and
	number of coats all affect the drying time.
	Touch dry (hours) : 1
	Dry to recoat (hours) : 2 - 4

APPLICATION DATA

APPLICATION METHOD	Brush, Roller or Spray	
THINNING (VOLUME)	5 - 10% depending on the method of application	
THINNER / CLEANER	Water	
AIRLESS SPRAY REQUIREMENTS	Pressure / Tip Size : 2000 - 2500 psi / 0.018" - 0.021"	
CONV. SPRAY REQUIREMENTS	Atomizing Pressure: 40 - 50 psi	
MIXING RATIO (VOLUME)	NA	
POT LIFE @ 30°C	NA	
RECOMMENDED SYSTEM	- National PVA Primer Sealer (or)	: 1 coat
	- National PVA Primer White	: 1 coat
	- National Stucco Filler (Interior)	: 2 coats
	- National Eggshell Emulsion (Matt)	: 2 coats

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.

