

**TECHNICAL SPECIFICATIONS**
**DECORATIVE COATINGS**
**TECHNICAL DATA SHEET**
**NATIONAL TENNIS COURT TOPCOAT**

<b>DESCRIPTION</b>	A high quality, alkali resistant acrylic co-polymer based paint. It is tough and abrasion resistant, National Tennis Court also contains antifungal and antibacterial additives.
<b>RECOMMENDED USE</b>	Used as a Tennis Court Paint, Car Parking and floor paint.

**TECHNICAL DATA**

<b>COLOURS</b>	As Per National Shade Card
<b>FINISH</b>	Matt
<b>VOLUME SOLIDS</b>	40 ± 2%
<b>SPECIFIC GRAVITY KG/L</b>	1.40 ± 0.05
<b>THEORETICAL SPREADING RATE</b>	8 M <sup>2</sup> /LTR
<b>RECOMMENDED (DFT) - MICRONS</b>	50 per coat
<b>RECOMMENDED (WFT) - MICRONS</b>	125 per coat
<b>DRYING TIME @ 30°C</b>	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 1
	Dry to recoat (hours) : 2 - 4

**APPLICATION DATA**

<b>APPLICATION METHOD</b>	Brush, Roller or Spray
<b>THINNING (VOLUME)</b>	10 - 15% depending on the method of application
<b>THINNER / CLEANER</b>	Water
<b>AIRLESS SPRAY REQUIREMENTS</b>	Pressure / Tip Size : 2100 psi / 0.018" - 0.021"
<b>CONV. SPRAY REQUIREMENTS</b>	Atomizing Pressure : 50 psi
<b>MIXING RATIO (VOLUME)</b>	NA
<b>POT LIFE @ 30°C</b>	NA
<b>RECOMMENDED SYSTEM</b>	- National PVA Primer Sealer (or) : 1 coat - National PVA Primer White : 1 coat - National Tennis Court Topcoat : 2 coats

**MISCELLANEOUS DATA**

<b>FLASH POINT</b>	Water Base
<b>SHELF LIFE @ 30°C</b>	18 months in original sealed containers, with proper storage conditions.

**NOTE :** We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.