

TECHNICAL SPECIFICATIONS
DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL TEX PRIMER

DESCRIPTION	A special Copolymer based, light textured, alkali resistant Primer with good sealing properties. Easy to apply and has excellent covering capacity. It contains antifungal and antibacterial additives.
RECOMMENDED USE	- Alkali resistant Primer for texture coatings. - General Purpose Primer for interior and exterior surfaces of concrete, plaster, gypsum, asbestos, wood, etc.

TECHNICAL DATA

COLOURS	White
FINISH	Matt
VOLUME SOLIDS	42 ± 2%
SPECIFIC GRAVITY KG/L	1.60 ± 0.05
THEORETICAL SPREADING RATE	9.5 M ² /LTR (Depends on Texture and Surface)
RECOMMENDED (DFT) - MICRONS	45 per coat
RECOMMENDED (WFT) - MICRONS	105 per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time. Touch dry (hours) : 1 Dry to recoat (hours) : 2 - 3

APPLICATION DATA

APPLICATION METHOD	Brush or Roller
THINNING (VOLUME)	15 - 20% depending on surface
THINNER / CLEANER	Water
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	- National PVA Primer Sealer (or) : 1 coat - National Tex Primer : 1 coat - Apply recommended system on top of Primer

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.