

DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL TEX (TEXTURED COATING)

DESCRIPTION	A texture coating based on a special Copolymer emulsion contains hard aggregate and marble chips, gives a heavy textured, water repellent, flexible finish with excellent alkali and weather resistance. It can cover uneven surfaces minor cracks, does not peel when the inner substrat moves. It can be overcoated with Nationalthane, National Polyurethane, National Acrylic Rock Topcoat. It contains antifungal and antibacterial additives.
RECOMMENDED USE	Texture coating for interior and exterior surfaces of concrete, plaster, masonry, brick work, asbestos, gypsum and wood

TECHNICAL DATA

COLOURS	As Per National Shade Card
FINISH	Matt, Heavy textured
VOLUME SOLIDS	66 ± 2%
SPECIFIC GRAVITY KG/L	1.80 ± 0.05
THEORETICAL SPREADING RATE	2 - 1 M ² /LTR
RECOMMENDED (DFT) - MICRONS	Depends on Texture and Surface
RECOMMENDED (WFT) - MICRONS	Depends on Texture and Surface
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 2 - 3
	Dry to recoat (hours) : 6 - 8
	Overcoating with any topcoat (hours) : Min. 24

APPLICATION DATA

APPLICATION METHOD	Roller
THINNING (VOLUME)	Ready for use, if required add 5 - 10% water.
THINNER / CLEANER	Water
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	- National PVA Primer Sealer (or) National Acrylic Primer (W.B.) : 1 coat (or) - National Tex Primer : 1 coat - National Tex (Textured Coating) : 1 coat

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.