

DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL TEX GLOSSY (TEXTURED COATING)

DESCRIPTION	Based on a high quality Copolymer emulsion and gives a textured flexible finish without any aggregate. It has very good resistance against humidity and UV rays. This hides and covers conveniently the unevenness in the surface. It contains antifungal and antibacterial additives.
RECOMMENDED USE	Texture coating for interior and exterior surfaces of concrete, plaster, wood, specially for portable cabins and false ceilings.

TECHNICAL DATA

COLOURS	As Per National Shade Card
FINISH	Satin texture
VOLUME SOLIDS	45 ± 2%
SPECIFIC GRAVITY KG/L	1.31 ± 0.05
THEORETICAL SPREADING RATE	1.5 - 1.0 M ² /LTR (Depends on Texture & Surface)
RECOMMENDED (DFT) - MICRONS	300 - 500 per coat
RECOMMENDED (WFT) - MICRONS	650 - 1100 per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 2
	Dry to recoat (hours) : 6 - 8

APPLICATION DATA

APPLICATION METHOD	Roller or Spray
THINNING (VOLUME)	Ready for use, if required 5% water can be added.
THINNER / CLEANER	Water
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	- National PVA Primer Sealer (or) National Acrylic Primer (W.B.) : 1 coat (or) - National Tex Primer : 1 coat - National Tex Glossy : 1 coat

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.