

TECHNICAL SPECIFICATIONS
DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL SPRAY PLASTER FINE

DESCRIPTION	National spray plaster is premixed plaster, based on special, water based binder, with smooth finish for uneven masonry surface. Also can be used on unplaster walls, block works etc. It contains antifungal and antibacterial additives.
RECOMMENDED USE	Is a ready to use plaster material for interior application on concrete, plaster, wood, walls, ceiling etc.

TECHNICAL DATA

APPEARANCE	Viscous paste
COLOURS	White
FINISH	Fine, smooth texture
VOLUME SOLIDS	57 ± 2%
SPECIFIC GRAVITY KG/L	1.68 ± 0.05
THEORETICAL SPREADING RATE	Depends on the thickness, porosity of surface
RECOMMENDED DFT	0.5 - 1.0 mm. per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affects the drying time
	Touch dry (hours) : 1 - 2
	Dry to recoat (hours) : 6 - 8

APPLICATION DATA

APPLICATION METHOD	Conventional spray plaster gun, putty knife
THINNING (VOLUME)	5 - 10% depending on thickness requirements
THINNER / CLEANER	Water for viscosity adjustment
RECOMMENDED SYSTEM	Remove dust, loose particles, grease, other foreign material. The ready plaster is to be applied directly, as required.
	- National Spray Plaster Coarse : One thick coat
	- National Spray Plaster Medium : One coat (or)
	- National Spray Plaster Fine : Two coats

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.