

**TECHNICAL SPECIFICATIONS**
**DECORATIVE COATINGS**
**TECHNICAL DATA SHEET**
**NATIONAL SPRAY PLASTER COARSE**

<b>DESCRIPTION</b>	National spray plaster is premixed plaster, based on special, water based binder, with rough finish for uneven masonry surface. Also can be used on unplaster walls, block works etc. It contains antifungal and antibacterial additives.
<b>RECOMMENDED USE</b>	Is a ready to use plaster material for interior application on concrete, plaster, wood, walls, ceiling etc.

**TECHNICAL DATA**

<b>APPEARANCE</b>	Viscous paste
<b>COLOURS</b>	Off White
<b>FINISH</b>	Rough texture
<b>VOLUME SOLIDS</b>	60 ± 2%
<b>SPECIFIC GRAVITY KG/L</b>	1.70 ± 0.05
<b>THEORETICAL SPREADING RATE</b>	Depends on the thickness, porosity of surface
<b>RECOMMENDED DFT</b>	1.0 - 1.5 cm per coat
<b>DRYING TIME @ 30°C</b>	Temperature, humidity, air movement, film thickness and number of coats all affects the drying time
	Touch dry (hours) : 1 - 2
	Dry to recoat (hours) : 24

**APPLICATION DATA**

<b>APPLICATION METHOD</b>	Conventional spray plaster gun, putty knife
<b>THINNING (VOLUME)</b>	5 - 10% depending on thickness requirements
<b>THINNER / CLEANER</b>	Water for viscosity adjustment
<b>RECOMMENDED SYSTEM</b>	Remove dust, loose particles, grease, other foreign material. The ready plaster is to be applied directly, as required.
	- National Spray Plaster Coarse : One thick coat
	- National Spray Plaster Medium : One coat (or)
	- National Spray Plaster Fine : Two coats

**MISCELLANEOUS DATA**

<b>FLASH POINT</b>	Water Base
<b>SHELF LIFE @ 30°C</b>	18 months in original sealed containers, with proper storage conditions.

**NOTE :** We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.