

TECHNICAL SPECIFICATIONS
DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL PVA PRIMER WHITE FOR MASONRY

DESCRIPTION	PVA-Acrylic Co-polymer based Penetrating Primer. Suitable for masonry surfaces especially formulated as a primer for texture spray system. It contains antifungal and antibacterial additives.
RECOMMENDED USE	-Primer for National Acrylic Rock, National Tile and National Eco System -General Purpose Primer for exterior and interior concrete, plaster, masonry, etc.

TECHNICAL DATA

COLOURS	White
FINISH	Smooth / Matt
VOLUME SOLIDS	35 ± 2%
SPECIFIC GRAVITY KG/L	1.46 ± 0.05
THEORETICAL SPREADING RATE	11.5 - 10 M ² /LTR
RECOMMENDED (DFT) - MICRONS	30 - 35 per coat
RECOMMENDED (WFT) - MICRONS	85 - 100 per coat
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time. Touch dry (hours) : 1 Dry to recoat (hours) : 2 - 3

APPLICATION DATA

APPLICATION METHOD	Brush or Roller or Spray
THINNING (VOLUME)	10 - 15% depending on method of application
THINNER / CLEANER	Water
MIXING RATIO (VOLUME)	NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	- National PVA Primer White for Masonry : 1 coat Then apply recommended system (or) - National Nutex (Spray Texture) : 1 coat - National Acrylic Rock Topcoat : 2 coat

MISCELLANEOUS DATA

FLASH POINT	Water Base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.