

**TECHNICAL SPECIFICATIONS**
**DECORATIVE COATINGS**
**TECHNICAL DATA SHEET**
**NATIONAL NUTEX (SPRAY TEXTURE)**

<b>DESCRIPTION</b>	A Copolymer Emulsion based, containing quartz fine aggregate giving a light/medium/heavy textured, weather resistant, flexible decorative finish. It contains antifungal and antibacterial additives.
<b>RECOMMENDED USE</b>	Intermediate coat for National Acrylic Rock, National Eco & National Tile Systems.

**TECHNICAL DATA**

<b>COLOURS</b>	White & Off White
<b>FINISH</b>	Matt, light / medium & heavy textured
<b>VOLUME SOLIDS</b>	65 ± 2%
<b>SPECIFIC GRAVITY KG/L</b>	1.60 ± 0.05
<b>THEORETICAL SPREADING RATE</b>	2.6 - 1.3 M <sup>2</sup> /LTR
<b>RECOMMENDED (DFT) - MICRONS</b>	250 - 500 per coat
<b>RECOMMENDED (WFT) - MICRONS</b>	385 - 770 per coat
<b>DRYING TIME @ 30°C</b>	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 4 - 6
	Dry to recoat (hours) : 24
	Overcoating with any topcoat (hours) : Min. 24

**APPLICATION DATA**

<b>APPLICATION METHOD</b>	Special Spray Gun or Roller
<b>THINNING (VOLUME)</b>	Ready for use
<b>THINNER / CLEANER</b>	Water
<b>SPRAY REQUIREMENTS</b>	Nozzle : 0.197" - 0.315" Atomizing Pressure : 60 - 70 psi
<b>MIXING RATIO (VOLUME)</b>	Base : Hardener : NA
<b>POT LIFE @ 30°C</b>	NA
<b>RECOMMENDED SYSTEM</b>	- National PVA Primer White for Masonry (or) : 1 coat - National Tex Primer : 1 coat - National Nutex (Spray texture) : 1 coat - Nationalthane /N. Polyurethane/N. Acrylic Rock/N. Weather resist : 2 coats

**MISCELLANEOUS DATA**

<b>FLASH POINT</b>	Water Based
<b>SHELF LIFE @ 30°C</b>	18 months in original sealed containers, with proper storage conditions.

**NOTE :** We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.