

**TECHNICAL SPECIFICATIONS**
**DECORATIVE COATINGS**
**TECHNICAL DATA SHEET**
**NATIONAL MARBERT FINISH**

<b>DESCRIPTION</b>	A decorative coating based on copolymer emulsion and can be applied in a variety of use to produce different pattern of finishes. Can be overcoated with Nationalthane Topcoat, National Gloss Emulsion & National Acrylic Rock Topcoat. It contains antifungal & antibacterial additives.
<b>RECOMMENDED USE</b>	Decorative coating for concrete, gypsum, wood and well prepared walls.

**TECHNICAL DATA**

<b>COLOURS</b>	White
<b>FINISH</b>	Smooth, Satin
<b>VOLUME SOLIDS</b>	60 ± 2%
<b>SPECIFIC GRAVITY      KG/L</b>	1.50 ± 0.05
<b>THEORETICAL SPREADING RATE</b>	3 - 2 M <sup>2</sup> /LTR
<b>RECOMMENDED (DFT) - MICRONS</b>	200 - 300 per coat
<b>RECOMMENDED (WFT) - MICRONS</b>	330 - 500 per coat
<b>DRYING TIME @ 30°C</b>	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 2
	Dry to recoat (hours) : 4 - 6

**APPLICATION DATA**

<b>APPLICATION METHOD</b>	Sponge roller, wire comb, texture gun, patterned roller
<b>THINNING (VOLUME)</b>	2 - 5%
<b>THINNER / CLEANER</b>	Water
<b>MIXING RATIO (VOLUME)</b>	Base: Hardener : NA
<b>POT LIFE @ 30°C</b>	NA
<b>RECOMMENDED SYSTEM</b>	- National PVA Primer White for masonry (or) : 1 coat - National Tex Primer : 1 coat - National Marbert Finish : 1 coat Topcoat: Nationalthane or Acrylic Rock or Gloss Emulsion : 2 coats

**MISCELLANEOUS DATA**

<b>FLASH POINT</b>	Water Base
<b>SHELF LIFE @ 30°C</b>	18 months in original sealed containers, with proper storage conditions.

**NOTE :** We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.