

**TECHNICAL SPECIFICATIONS**
**DECORATIVE COATINGS**
**TECHNICAL DATA SHEET**
**NATIONAL MULTICOLOUR GLAZE COAT**

<b>DESCRIPTION</b>	Acrylic copolymer emulsion based clear coating to be used as seal coat on multi-colour finish to enhance the richness of finish and to add sheen. It contains antifungal & antibacterial additives.
<b>RECOMMENDED USE</b>	Topcoat for National Multi-colour.

**TECHNICAL DATA**

<b>COLOURS</b>	Clear
<b>FINISH</b>	Smooth, Semi glossy
<b>VOLUME SOLIDS</b>	25 ± 2%
<b>SPECIFIC GRAVITY KG/L</b>	1.05 ± 0.05
<b>THEORETICAL SPREADING RATE</b>	8 M <sup>2</sup> /LTR
<b>RECOMMENDED (DFT) - MICRONS</b>	30 per coat
<b>RECOMMENDED (WFT) - MICRONS</b>	120 per coat
<b>DRYING TIME @ 30°C</b>	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (hours) : 2
	Dry to recoat (hours) : 4

**APPLICATION DATA**

<b>APPLICATION METHOD</b>	Roller
<b>THINNING (VOLUME)</b>	Ready to use
<b>THINNER / CLEANER</b>	Water
<b>MIXING RATIO (VOLUME)</b>	Base : Hardener : NA
<b>POT LIFE @ 30°C</b>	NA
<b>RECOMMENDED SYSTEM</b>	- National PVA Primer Sealer / Primer White : 1 coat - National Stucco Filler : 2 coats - National Matt Emulsion : 1 coat - National Multi Colour : 1 coat - National Multi Colour Glaze Coat : 1 coat

**MISCELLANEOUS DATA**

<b>FLASH POINT</b>	Water base
<b>SHELF LIFE @ 30°C</b>	18 months in original sealed containers, with proper storage conditions.

**NOTE :** We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.