

DECORATIVE COATINGS

TECHNICAL DATA SHEET

NATIONAL NATURAL FURNITURE FILLER

DESCRIPTION	Is a special wood filler, with faster drying properties. Specially developed, based on nitro cellulose, alkyd resins and extenders combination
RECOMMENDED USE	Mainly for hardwood and MDF surfaces, for filling up open grains to obtain a smooth even surfaces. For dent and gap filling in wood working.

TECHNICAL DATA

COLOURS	Natural
FINISH	Matt
VOLUME SOLIDS	40 ± 2%
SPECIFIC GRAVITY KG/L	1.25 ± 0.05
THEORETICAL SPREADING RATE	As per DFT required
RECOMMENDED (DFT)	Maximum 2 to 3 mm
RECOMMENDED (WFT)	Maximum 4 to 5 mm
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affects the drying time.
	Touch dry (minutes) : 20 - 30
	Dry to recoat (hours) : 1 - 2
	Hard dry (hours) : 4 - 5

APPLICATION DATA

APPLICATION METHOD	Glazing Knife, Spatula
THINNING (VOLUME)	Ready to use
THINNER / CLEANER	National Lacquer Thinner
MIXING RATIO (VOLUME)	Base: Hardener : NA
POT LIFE @ 30°C	NA
RECOMMENDED SYSTEM	- National N.C. Sanding Sealer : 2 coats - National Natural Furniture Filler : 2 coats - National N.C. Auto Lacquer Topcoat : 2 coats

MISCELLANEOUS DATA

FLASH POINT	7°C
SHELF LIFE @ 30°C	12 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.