

DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL FIBRE

DESCRIPTION	National fibre wall covering are mainly used for interior decoration application. These fibres are based on fibre glass filaments. Useful for getting different pattern, can be painted using various systems.
RECOMMENDED USE	<ul style="list-style-type: none"> - Suitable for painting for all interior surfaces. - Renovation of old buildings, houses. - For decoaration of restaurants, hotels, banks etc.

TECHNICAL DATA

NATIONAL FIBRE (FIBER GLASS FABRIC)	WEIGHT (g / sq.m)	SIZE
N - 103	110	In roll of 50 metres by one metre
N - 022	165	“
N - 058	180	“
N - 060	180	“
N - 064	180	“
N - 073	180	“
N - 090	180	“
N - 095	180	“
N - 0490	210	“
N - 0550	210	“
N - 0530	210	“
N - 0570	210	“
N - 0580	210	“

APPLICATION PROCEDURE	<ul style="list-style-type: none"> - Apply National Primer Sealer. Allow it to dry. - Apply National White Glue. - Fix National fibre while the glue is still wet. - Apply first coat of National Matt Emulsion Paint (OR) National Acrylic Rock Topcoat. - Apply second coat of National Matt Emulsion Paint (OR) National Acrylic Rock Topcoat. - For more details please refer to National Fibre Brochure.
------------------------------	---

MISCELLANEOUS DATA

DRYING TIME @ 30°C 20 - 22 HOURS	Application of National White Glue, then fixing of National Fibre, Application of Topcoat.
---	---

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.