




Tile and Stone Installations

11/200

Waterproofing

System Solutions for Bathrooms



Waterproofing

In wet areas tile and stone installations are typically used as floor and wall coverings. Tiles and stones are moisture-resistant and water-repellent. However the joint grouts used are permeable to water at least in a way, that an additional waterproofing material is required to prevent prospective damages in the construction.

Knauf waterproofing materials protect moisture sensitive substrates in wet areas which are not exposed to pressurized water. Typical fields of applications are bathrooms, showers in residential buildings, hotels, old people's homes, hospitals and rooms with similar domestic use.

Knauf waterproofing materials are highly flexible, are able to compensate tensions as well as variations in temperature and deformations of the substrate. An excellent crack-bridging behavior offers high security even when subsequent cracks occur in the substrate.

Knauf waterproofing materials can either be used on moisturesensitive, absorbent substrates like plasters, plaster slabs, gypsum fiber boards, plaster boards, anhydrite screeds and on absorbent mineral substrates like concrete, screed, render, aerated concrete and cement boards.



Priming absorbent mineral or gypsum-based substrates and plaster boards with Knauf Primer



In corner areas Knauf Waterprofing Corner is embeded in a fresh applied coating of Knauf Waterproofing. Pipe connection are sealed with Knauf Pipe-Lead-in Gaskets.



In case of wall/wall and floor/wall junctions Knauf Waterproofing Tape is applied the same way.



Apply undiluted Knauf Waterproofing to the substrate as a first protective coating to cover the entire surface.



After complete curing of the first coating (approx. 6h) a second coating of Knauf Waterproofing is necessary.



When the second coating of Knauf Waterproofing has cured completely, tiles and stones can be installed.

Knauf Waterproofing

• Polymer dispersion based waterproofing material to receive ceramic tiles and natural stones.

• Use for residential and light commercial showers, bathrooms and other rooms with similar moisture treatment.

 Also to receive ceramic tiles and natural stones on heated substrates (floor and wall heating).

• Crack bridging up to 2mm: to offer high security even in cases of subsequent cracks.

- Prevents moisture from above.
- Ready to use and solvent free. Compatible to silicones.

Knauf Waterproofing Accessories:

- Knauf Waterproofing Tape
- Knauf Waterproofing Corner
- Knauf Pipe Lead-in Gasket





The content of this technical data sheet corresponds to our knowledge at time of printing. Technical data sheets are actualized regularly. The relevant version is available on our web page or by calling our Technical Service Department. Knauf Bauprodukte, does not authorize anyone, including Knauf Bauprodukte Representatives, to make any statements which supersede, modify or supplement the information provided on its printed literature or package labels without written confirmation from Knauf Bauprodukte Technical Service Department. Knauf Bauprodukte makes no warranty of merchantability or suitability of its products for any particular purpose. All product demonstrations are placed for illustrative purposes only and do not constitute a warranty of any kind. Knauf Bauprodukte sells its products upon the condition that customers shall conduct their own tests to determine the suitability of the products for the customers' intended purposes. Under no circumstances will Knauf Bauprodukte be liable for economic, special, incidental, or consequential damages or lasses of any kind whatsoever arising out of or occasioned by the selection, use, installation, or replacement of these products.



Knauf Bauprodukte GmbH & Co. KG Technical Support:

Phone: +49 (0) 9323 31-247

Fax: +49 (0) 9323 31-1024

www.knauf-bauprodukte.de www.buildingchemicals.de

Tile and Stone Installations

BPBC001/eng/intermediell/11.08