

BAV 86

Ball valve – DN 15-50



Ball valve for heating and cooling systems. Available in the pressure classes PN 40 and PN 32.

TA-SC

Distributed by TA Hydraulics



Technical description

Applications:

Heating and cooling systems

Function:

Shut-off

Dimensions:

DN 15-50

Pressure class:

PN 40 (DN 15-25)

PN 32 (DN 32-50)

Temperature:

Max. working temperature: 120°C

Min. working temperature: 0°C

Material:

Body: Copper alloy DZR CuZn36Pb2As (EN 12165)

Spindle: Copper alloy DZR CuZn36Pb2As (EN 12165)

Ball: Copper alloy (chromed) DZR CuZn36Pb2As (EN 12165)

Seal: PTFE

Spindle seal springs: EPDM O-ring

Lever: Iron, coated with zinc and plastified

Marking:

TA-SC, PN, DN and year of production.


Colour:

Handle: Red

Articles

Female threads

Threads according to ISO 228



Article No	DN	D	L1	L2	H	Kg
PN 40						
78 620-015	15	G1/2	58,5	92	41	0,20
78 620-020	20	G3/4	67,5	92	46	0,30
78 620-025	25	G1	80	120	55,5	0,49
PN 32						
78 620-032	32	G1 1/4	96	120	63	0,76
78 620-040	40	G1 1/2	106	150	80	1,1
78 620-050	50	G2	130	150	88	1,9

The products, texts, photographs, graphics and diagrams in this brochure may be subject to alteration without prior notice or reasons being given.

For the most up to date information about our products and specifications, please visit www.tahydraulics.com.

2-60-5 BAV 86 03.2011