

NRV 27

Swing check valve – DN 15-50



Swing check valve for heating and cooling systems. Available in pressure class PN 16.

TA-SC

Distributed by TA Hydraulics



Technical description

Applications:

Heating and cooling systems

Function:

Uni-directional flow

Dimensions:

DN 15-50

Pressure class:

PN 16

Temperature:

Max. working temperature: 95°C

Min. working temperature: 0°C

Material:

Body: Bronze CuSn5Zn5Pb5-c (EN 1982)

Cap: Copper alloy CuZn40Pb2 (EN 12165)

Flap: Copper alloy CuZn40Pb2 (EN 12165)

Seals: NBR (DN 15-25), PTFE (DN 32-50)


Marking:

TA-SC, PN, RG5, size (inch) and flow direction arrow.

Articles

Female threads

Threads according to ISO 228



Article No	EAN	DN	D1	D2	L	H	Kg
78 630-015	7318793960504	15	G1/2	14	55	36	0,20
78 630-020	7318793960603	20	G3/4	20	62	43	0,34
78 630-025	7318793960702	25	G1	25	72	49	0,48
78 630-032	7318793960801	32	G1 1/4	30	82	57	0,69
78 630-040	7318793960900	40	G1 1/2	35	90	63	0,90
78 630-050	7318793961006	50	G2	47	105	69	1,3

The products, texts, photographs, graphics and diagrams in this brochure may be subject to alteration without prior notice or reasons being given.

For the most up to date information about our products and specifications, please visit www.tahydraulics.com.

16-10-5 NRV 27 03.2011