

### DESCRIPTION:

A classical luxurious water-borne paint formulated to obtain coral-like structure.

### RECOMMENDED USE:

Recommended to be used for interior application as a finish coat over "Al-Jazeera Khayal Primer" on concrete, cement and gypsum surfaces. The places where this product can be applied are palaces, offices, showrooms, hotels, restaurants, galleries etc.

### CHARACTERISTICS:

"Al-Jazeera Khayal" has the following features:

- Wide range of colours.
- The product itself offers Coral-like effect which personalizes this product.
- Gives you a feeling to be close to the nature.
- Selection of shades will reflect one's vision in how he /she wants nature look-like.
- Excellent adhesion and high durability properties.
- Washable.

### PHYSICAL CONSTANTS:

Finish:	Coral-like structure.
Colour:	Available as per catalog.
Specific Gravity:	1.05±0.03 at a temperature of 30±2°C. ASTM D-1475.
Viscosity:	high viscous.
Theoretical Spreading Rate:	5-7 m <sup>2</sup> /ltr (per coat) (200.5-280.7 ft <sup>2</sup> / US gallon). (To avoid waste, be sure to buy the right amount of the paint for the surface area required).
Heater Stability:	Pass 49 days at 50°C.

### SURFACE PREPARATION:

#### New surfaces

- All new surfaces must be cured at least for 30 days prior to application of the primer.
- The surface must be treated by removing all forms release and protrusions to get a suitable surface for application.

#### For previously painted surfaces:

- Remove old paint from surfaces completely.
- Make sure that the surface is clean, dry, and free from dust, oil, grease, salt and mold.
- Fill the holes and cracks with suitable fillers "Al-Jazeera Crack Filler" prior to application of the primer.

### APPLICATION GUIDE:

- 1.The surface must be removed from dust, grease, oil and other contaminants completely.
- 2.Surface temperature required during application must not be less than 10°C; the surface moisture should not exceed 8% and the relative humidity at work place not to exceed 70%.
- 3.Maximum pH of 9.
- 4.Paint should be stirred carefully before use.
- 5.Do not apply on wet and moistened surfaces until get completely dry.
- 6.Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be given between the two coats.

7.Adequate ventilation should be provided during drying time.

### APPLICATION TOOLS:

Brush: Recommended type: Special type  
Plastic scrapper: Recommended type: Special type.

### THINNER:

Not recommended.

### THINNING RATIO:

Not recommended.

### PAINTING SYSTEM:

- Apply one coat of "Al-Jazeera Primex" or any other suitable type of Al-Jazeera Primers, depending on surface and leave for full dry.
- Apply two coats of "Al-Jazeera Easy Putty".
- Apply two coats of "Al-Jazeera Khayal Primer", of the same color as that of "Al-Jazeera Khayal Base", by using a fine roller or spray gun and make sure that surface is uniform and there are no roller marks.
- Apply two coats of "Al-Jazeera Khayal Base".
- The color of "Al-Jazeera Khayal Primer" must always be the same as "Al-Jazeera Khayal Base".
- Applying the product obliquely by cross (X) method by special recommended brush.
- Press gently by the same method by special recommended plastic scrapper

### DRYING TIME:

Surface dry	(10 - 15) minutes.
-Full dry	5 hours.
-Hard dry	24 hours.

All above test results according to ASTM D5895 @25°C.

### CLEANING TOOLS:

Tap water.

### PACKING:

2.5 liters Liquid plastic container.

### SHELF LIFE:

In sealed container: 12 months in a dry, cool and well-ventilated place.

### SAFETY PRECAUTIONS:

During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided. When working with paint in insufficient ventilated areas, forced ventilation should be provided. For spray application system, eye, skin, respiratory protection are always recommended. Keep away from the reach of children.

For environmental safety, please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

Note: Wastes and empty containers should be disposed of in accordance with local regulations made under the Control of Pollution Act and the Environmental Protection Act.