

DESCRIPTION:

A final coat with textured appearance, based on acrylic emulsion. It gives strong, homogenous and attractive finish in single coat with long furrows line to provide a beautiful decorative finish.

RECOMMENDED USE:

Recommended to be used as a final coat for exterior applications on concrete, cement and brick surfaces, over any suitable type of Al-Jazeera paints primers. Also, it could be used for interior application.

CHARACTERISTICS:

"Al-Jazeera Lintex " has the following features:

- High resistance to moisture, temperature and weather conditions.
- High resistance to scratch and friction.
- Easy to apply and formation in different shapes.
- Color retention
- Excellent adhesion to the surfaces.

PHYSICAL CONSTANTS:

Finish:	Matt, grooved texture.
Colour:	Produced in white and other colours of Al-Jazeera colour card.
Specific Gravity:	1.9 At temperature of 25°C.
Viscosity:	High viscous.
Volume solid:	82 %, ASTM D2697.
Theoretical Spreading Rate:	(0.15 – 0.20) m ² / Kg. (0.29 – 0.38 m ² / ltr) (11.43 – 15.24 ft ² / US gallon). Depending on the design, thickness of the coat, nature of the surface and application conditions.
VOC:	15.3 g/ltr.

SURFACE PREPARATION:

New surfaces

- All new surfaces must be cured at least for 30 days prior to application of the primer.
- The surface must be treated by removing all forms release and protrusions to get a suitable surface for application.

For previously painted surfaces:

- Remove old paint from surfaces completely.
- Make sure that the surface is clean , dry , free from dust, oil, grease, salt and mold.
- Fill the holes and cracks with suitable fillers "Al-Jazeera Crack Filler" prior to application of the primer.

APPLICATION GUIDE:

- 1.The surface must be removed from dust , grease, oil and other contaminants completely.
- 2.Surface temperature required during application must not be less than 10°C; the surface moisture should not exceed 8% and the relative humidity at work place not to exceed 70%.
- 3.Maximum pH of 9.
- 4.Paint should be stirred carefully before use.
- 5.A suitable quantity of water can be added to get reasonable viscosity for application.
- 6.Do not apply on wet and moistened surfaces until get completely dry.
- 7.Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be given between the two coats.

APPLICATION TOOLS:

Steel trowel:	Recommended type: Steel plain trowel.
Plastic trowel:	Recommended type rough and soft plastic plain trowels.

THINNER:

Recommended thinner is: " Tap Water ".

THINNING RATIO:

Ready to use.
(1 - 2)% of tap water can be used for thinning if required. Depending on the weather and application conditions.

PAINTING SYSTEM:

- Apply one coat of "Al-Jazeera Primex" or any other suitable type of Al-Jazeera primers, depending on the surface and leave for full dry.
- Apply one coat of "Al-Jazeera Linetex" by steel trowel.
- Make the required design by the rough plastic trowel; clean the trowel from time to time during application with a sponge saturated with tap water.
- Smooth the surface and make it uniform by soft plain plastic trowel to get the desired beautiful and uniform appearance (if required).

Notes:

- 1-" Al-Jazeera linetex" should be applied by professional painter to get the desired design and spreading rate.
- 2-During application sufficient pressure should be by trowel for strong adhesion.
- 3-For any bend or circular surfaces has to be given more attention during application.

DRYING TIME :

- Surface dry	2 Hrs.
- Full dry	24 Hrs.
- Hard dry	48 Hrs.

All above results according to ASTM D5895.

CLEANING TOOLS:

Sponge saturated with tap water.

PACKING:

- 25 Kg. Drums.

SHELF LIFE:

In sealed container: 12 months in a dry, cool, and well-ventilated place.

SAFETY PRECAUTIONS:

During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist, should be strongly avoided. When working with paint in in-sufficient ventilated areas, forced ventilation should be provided. For spray application system, eye, skin, respiratory protection are always recommended. Keep away from the reach of children.

For environmental safety: please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

Note: Wastes and empty containers should be disposed of in accordance with local regulations made under the Control