// New: now 6 attractive entrance door styles



Comfort Front Doors

Attractive aluminium doors, extremely fast and inexpensive



The HÖRMANN Range of Comfort Aluminium Front Doors with the Distinct, Timeless Aesthetics and Superior Quality Features.

This series of good-value front door models featuring proven Hörmann technology and UPVC infills can be supplied in 8 or 13 days depending on the choice of model and equipment options. A convincing argument for any homeowner.

8 working days approx.delivery time

Single-leaf front doors with the handles, lock and equipment options as illustrated, as well as the described glass type, version in white RAL 9016.

Max. dimensions: 1150 x 2250 mm (W x H).

You will find a comprehensive assortment of TopComfort and TopPrestige aluminium front doors on the Internet at www.hoermann.com.



13 working days approximately time

Comfort front doors are available with fixed side element and/or transom light and/or letter box systems with the insulated glass types as side element glazings described below:

outside clear Float

inside choice of clear Float Mastercarré Parsol grey sand-blasted Float sand-blasted Parsol grey

Available sizes:

Max. width:
as per the current Hörmann price list, however, side elements with UPVC infills (K) 950 mm.

Max. height:
2250 mm without transom light,
2400 mm with transom light
(horizontal rail construction),
2800 mm with transom light
(preconnected).

Overview of HÖRMANN Comfort Aluminium Front Doors with UPVC Infills.

Style 900 C





900 C

UPVC infill Insulated glass, outside clear Float, inside Mastercarré Handle 38-2



902 C

UPVC infill Insulated glass, outside clear Float, inside Mastercarré Handle 38-2



904 C

UPVC infill Insulated glass, outside clear Float, inside sandblasted Float with clear horizontal stripe Handle 38-2









906 C

UPVC infill
Insulated
glass,
outside
clear Float,
inside sandblasted
Parsol grey
with clear
horizontal
stripe
Handle 38-2



975 C

UPVC infill Insulated glass, outside clear Float, inside Mastercarré Handle 38-2











t goes without saying that you have the opportunity of designing your own "dream door" by selecting further optional extras. Whether it's a special door handle, an electric door opener or additional security, Hörmann Comfort front doors will meet your every requirement.

Door handles



Security packs

As an alternative to the standard three-point lock, the Comfort front doors are also available with an automatic lock (self-locking) and an automatic multiple-point lock (self-locking).

Other optional extras

- Stainless steel interior lever handle with cylinder rose
- Electric door opener
- Overhead door closer with hold-open function
- Rounded fascia frame outside
- Stainless steel bottom section for door and side element



Stainless steel Interior lever handle



Rounded fascia frame Stainless steel Bottom section

State-of-the art Engineering and Quality in Every Detail.

- Sturdy triple chamber profiles (overall thickness 80 mm) for heavy duty
- High thermal insulation meets the requirements of the energy-saving regulation EnEV
- Double door seal ensures excellent sealing properties and good acoustic insulation
- A special surface finish prevents the UPVC infills from turning yellow



Increased security thanks to two-piece, three dimensionally adjustable hinges with plastic bushes and stainless steel pivot.



Elegant white cylinder rose



Three-point-security lock

The security lock not only secures the door via a latch and bolt but additionally via two steel hook-swivel bolts (top and bottom) making sure that the Comfort front door is secured at 3 different points with just one turn of the key.



Hörmann Comfort front doors are protected by copyright. Subject to technical changes and further

developments as well as variations in colour and design.

No part of this brochure may be reproduced without our permission.



Exceptionally sturdy and thermally insulated, 80 mm wide front door threshold

· Water-tight, thermally insulated threshold area thanks to a double lip buffer seal in conjunction with sealing form parts