

Comshade®

EXTRA HEAVY DUTY
KNITTED SHADECLOTH



COMSHADE® is a unique and innovative extra heavy duty knitted shade cloth. It is designed for tension membrane shadesails used in architectural and commercial shade structures. It is UV stabilised to maintain its strength and flexibility under the harsh Australian sun.

**Aiming high
to reduce
the risks**

Australia and New Zealand are recognised as having the world's highest incidences of melanoma and skin cancer. This is why Polyfab is so determined to make and supply the world's best shade cloth for the protection of people from the sun's harmful UV rays.




polyfab™
Australia

Comshade® EXTRA HEAVY DUTY KNITTED SHADECLOTH



Comshade® is ideal for large commercial projects where the fabric is supported by engineering certification, that allows the knitted shadecloth to be placed under higher tensile loadings.

Comshade® offers excellent weight to strength ratios.

Comshade® is heat set, making it much easier to use. It lays very flat so it will not curl or roll up when being marked out, cut and sewn. This means major savings in time and fabrication costs.

Comshade® has less shrinkage and is more stable, while maintaining its strength and over 90% UV protection and shade factors.

Comshade® comes in an excellent range of 16 designer colours.

Comshade® is made to the highest quality standards, and is supported by a 10 Year UV warranty.

Comshade® is made from virgin resins and only the best UV stabilizers from Ciba Speciality Products.

For information and conditions of the warranty, contact your local stockist or visit our web site at www.polyfab.com.au for warranty and maintenance instructions.

Comshade® is made to Australian Standards: AS 4174-1994



Comshade® is available in 16 designer colours.



Colour Disclaimer: For technical reasons connected with colour reproduction, the colours shown may not be an exact representation of the actual product.

Technical Specifications		WARP	WEFT
Breaking Force	N/50mm	799	2147
Breaking Extension	%	83.5	63.0
Tear Resistance (Wing Tear)	N	172	282
Bursting Force (Steel Ball)	Mean N		1861
Bursting Pressure	Mean kPa		3000

Colours	UVR%	Mean UPF	Shade Factor (Visual Light) %
● Porcelain	96.1	41	77
● Cappuccino	95.2	34	90
○ Café Noir	96.1	44	94
○ Sandstone	95.2	28	87
○ Rust	95.7	27	90
○ Copper	96.4	44	92
○ Merlot	96.7	41	96
○ Yellow	97.4	55	79
● Aquamarine	95.8	35	93
○ Navy Blue	98.2	99	98
● Black	95.5	40	96
● Slate	96.8	42	96
● Blue Gum	96.1	44	94
○ Platinum	93.8	17	94
○ Light Green	94.9	19	89
● Midnight Green	95.4	35	95

Manufacturer reserves the right to modify specifications or colors without notice. All specification tolerances +/- 5%

Available in:	3.80 x 30m Centre folded rolls	3.80 x 50m Straight rolls	● 6 x 30m Straight rolls
---------------	-----------------------------------	------------------------------	-----------------------------

Average weight: 330gsm

Distributed by: **Nolan.UDA** www.NolanUDA.com.au

PERTH
18 Hazelhurst Street,
Kewdale, WA 6105
Tel: (08) 9353 2534
Fax: (08) 9353 1215

DARWIN
Unit 1, 6 Finnis Street,
Darwin, NT 0800
Tel: (08) 8981 1555
Fax: (08) 8981 1533

SYDNEY
3 Bradford Street,
Alexandria, NSW 2015
Tel: (02) 9669 3333
Fax: (02) 9669 3266

BRISBANE
14 Lions Park Drive,
Yatala, QLD 4207
Tel: (07) 3387 8500
Fax: (07) 3807 8300

ADELAIDE
489 Cross Keys Road,
Cavan, SA 5094
Tel: (08) 8260 1055
Fax: (08) 8260 1655

NEWCASTLE
66 Orlando Road,
Lambton, NSW 2299
Tel: (02) 4957 7766
Fax: (02) 4952 6737

MELBOURNE
55 Cleeland Road,
Oakleigh South, VIC 3167
Tel: (03) 9545 5588
Fax: (03) 9545 5582



Polyfab Australia Pty Ltd
ABN 54 069 432 846
63 Frankston Gardens Drive
Carrum Downs VIC 3201 Australia
Telephone 03-9770 8480
Facsimile 03-9770 8483
www.polyfab.com.au