



Wood, magnesite and water are the principal components of the Heradesign® acoustic panels - so they are completely harmless in terms of building biology. Heradesign's® magnesite bonded wood wool panel is a natural product in line with the current trend for sustainable materials. Besides studying the phenomenon of noise and acoustics, for us this means the development of sustainable, acoustically optimised solutions. Acoustics is one of the most important factors that influences the well-being, mood and temper of people - even if we do not perceive it consciously.

Heradesign® acoustic panels can prove a durability of more than 80 years in buildings. In case it should one day become necessary: magnesite bonded wood wool panels can also be recycled. Because, when talking about sustainability in the building industry, the topic of disposal is becoming more and more important. Acoustics and design with a clear, 'green conscience'!





















Heradesign® product world



Business unit of Knauf AMF Deckensysteme GmbH

A-9702 Ferndorf 29, Austria

Tel.: +43 4245 2001 3003 Fax: +43 4245 2001 3499

office@heradesign.com www.heradesign.com

the information provided. Subject to change.





AMF and Heradesign® – two strong partners of the Knauf Group, combine their expert knowledge and skills in ceiling and wall solutions. Together they provide specialist planners, architects and clients all over the world with the best possible sales and consultation services, as well as a sophisticated product range.





sustainable acoustic solutions for well-being room atmosphere

Heradesign® produces, develops and distributes high-class acoustic systems based on wood wool for ceiling and wall installations. The main areas of application of the Heradesign® acoustic systems are: education, sports, office, infrastructure, entertainment and recreational facilities.



Product Overview

Heradesign® *macro*



1-layer magnesite bonded wood wool acoustic panel (fibre width approx. 3 mm)

- characteristic surface structure building biology recommended

Heradesign® *micro*



1-layer magnesite bonded wood wool acoustic

- panel with a fine pored structure
- building biology recommended

Heradesign® *fine* Heradesign® fine A2



1-layer magnesite bonded wood wool acoustic panel (fibre width 2 mm)

- characteristic surface structure - acoustically effective
- building biology recommended

Heradesign® *plano*



1-layer magnesite bonded wood wool acoustic

- building biology recommended
- panel with closed surface

Heradesign® superfine Heradesign® superfine A2



- 1-layer magnesite bonded wood wool acoustic panel (fibre width approx. 1 mm)
- exquisite surface structure - building biology recommended

Heradesign® *plus*



Composite product consisting of a magnesite bonded wood wool acoustic panel and a mineral wool absorber

- excellent sound absorption values - with trickle protection
- easier and faster installation

Product Range

| Product Range | | | | | | | | Product Range A2 | | Product Range plus | | | |
|---|----------|---------------|--|------------|------------|------------|------------|------------------|-------------|------------------------------|----------------|------------|------------|
| | | | macro | fine | superfine | micro | plano | fine A2 | superfineA2 | fine plus | superfine plus | micro plus | plano plus |
| Nominal size mm (further sizes on request) 600 x 600 mm 625 x 625 mm 1200 x 600 mm 1250 x 625 mm | | • | • | • | • | • | • | • | _ | _ | _ | _ | |
| | | 625 x 625 mm | _ | • | • | • | • | _ | _ | _ | _ | _ | _ |
| | | 1200 x 600 mm | • | • | • | • | • | • | • | • | • | • | • |
| | | 1250 x 625 mm | _ | • | • | • | • | _ | _ | _ | _ | _ | _ |
| Panel thicknesses | 1-layer | 15 mm | _ | • | • | _ | _ | • | • | _ | _ | _ | _ |
| | | 25 mm | • | • | • | • | • | • | • | _ | _ | _ | _ |
| | | 35 mm | _ | • | • | • | _ | _ | _ | _ | _ | _ | _ |
| | 2-layers | 40 mm (15/25) | _ | _ | _ | _ | - | _ | _ | • | • | _ | _ |
| | | 50 mm (25/25) | _ | _ | _ | _ | _ | _ | _ | • | • | • | • |
| | | 55 mm (15/40) | _ | _ | _ | _ | _ | _ | _ | • | • | _ | _ |
| | | 65 mm (25/40) | _ | _ | _ | _ | _ | _ | _ | • | • | • | • |
| Reaction to fire according to EN 13501-1: B-s1, d0 | | | • | • | • | • | • | _ | _ | • | • | • | • |
| Reaction to fire according to EN 13501-1: A2-s1, d0 | | | _ | _ | _ | _ | _ | • | • | _ | _ | _ | _ |
| Sound absorption value | | | | | | | | | | | | | |
| Weighted sound absorption coefficient $\alpha_{\mbox{\tiny W}}$ | | | up to 0,70 | up to 0,90 | up to 1,00 | up to 0,55 | up to 0,35 | up to 0,75 | up to 0,95 | up to 0,85 | up to 0,95 | up to 0,35 | up to 0,40 |
| Noise reduction coefficient NRC | | | up to 0,75 | up to 0,95 | up to 1,00 | up to 0,60 | up to 0,35 | up to 0,75 | up to 1,00 | up to 0,85 | up to 0,95 | up to 0,35 | up to 0,45 |
| Product declaration | | | | | | | | | | | | | |
| WW-EN 13168-L3-W2-T2-S3-P2-CS(10)200-Cl3 | | | • | • | • | • | • | • | • | _ | _ | _ | _ |
| WW-EN 13168-L3-W2-T2-S3-P2-CS(10)20-TR5-Cl3 | | | _ | _ | _ | _ | - | _ | _ | • | • | • | • |
| EC Conformity Certificate Reg. No.: | | | K1-0751-CPD-209.0-01-01/2011 | | | | | | | K1-0751-CPD-209.0.02-01/2009 | | | |
| Standard colours | | | white, similar to RAL 9010 / beige - natural tone 13 (further colour shades from colour systems such as RAL, NCS, BS or StoColor available) | | | | | | | | | | |
| Areas of application | | | suitable for rooms with a constant relative humidity of up to 90%. Application in rooms with relative humidity higher than 80% requires consultation with structural-physical experts. | | | | | | | | | | |

Systems and system parts



Product attributes













Humidity and



Edge design







endless scope









non-combustibility A2

Dimensional accuracy

and tolerances

sustainable raw

Colors

An almost unlimited range of colours is available – almost every colour from popular colour systems such as RAL, NCS or StoColor can be chosen.