



DWA8011R 355mm CHOPSAW WHEEL





30%

Four High Durability Ring Holding points – Uniform stress on the Disc which avoids breakage

Single reinforced Design – Value for money

DIAMETER	355mm
THICKNESS	3mm
ARBOR	25.4mm
GRIT	A30RBF
APPLICATION	Fast General Purpose Metal Cutting
MAX RPM	4,400
РАСК	10

APPLICATIONS:

- Burr free cutting in ferrous materials.
- Suitable for construction applications like Re-bar cuting, hollow pipe cutting for grills.

FEATURES:

- Thin wheel design for burr free cutting 3mm thickness.
- Aluminum oxide formulation for fast cutting.

DEWALT

Ø355x3x25.4mm

MAX RPN

4,400 MAX 80m/s

DWA8011R

A30RB

EN12413

GUARANTEED TOUGH.



HSS-G DIN 338 JOBBER METAL DRILL BIT

LIST OF HSS-G DIN 338 JOBBER METAL DRILL BITS

Cat No	Diameter	Length	Working	Pack
	mm	mm	Length mm	Qty
DT50465-XJ	1.0	34	12	10
DT50466-XJ	1.5	40	18	10
DT50467-XJ	1.6	43	20	10
DT50468-XJ	2.0	49	24	10
DT50469-XJ	2.5	57	30	10
DT50470-XJ	3.0	61	33	10
DT50471-XJ	3.2	65	36	10
DT50472-XJ	3.5	70	39	10
DT50473-XJ	4.0	75	43	10
DT50474-XJ	4.5	80	47	10
DT50475-XJ	4.8	86	52	10
DT50476-XJ	5.0	86	52	10
DT50477-XJ	5.5	93	57	10
DT50478-XJ	6.0	93	57	10
DT50480-XJ	6.5	101	63	10
DT50481-XJ	7.0	109	69	10
DT50482-XJ	7.5	117	75	10
DT50483-XJ	7.9	117	75	10
DT50484-XJ	8.0	117	75	5
DT50485-XJ	8.5	117	75	5
DT50486-XJ	9.0	125	81	5
DT50487-XJ	9.5	125	81	5
DT50488-XJ	10.0	133	87	5
DT50489-XJ	10.5	133	87	5
DT50490-XJ	11.0	142	94	5
DT50491-XJ	11.5	142	94	5
DT50492-XJ	12.0	151	101	5
DT50493-XJ	12.5	151	101	5
DT50494-XJ	13.0	151	101	5
DT50495-XJ	14.0	160	108	1
DT50496-XJ	15.0	169	114	1
DT50497-XJ	16.0	178	120	1
DT50498-XJ	18.0	191	130	1
DT50499-XJ	20.0	205	140	1

DEWALT is extending its high-performance technology to include the new HSS-G DIN 338 Jobber Metal Drill Bits Series. Its groundbreaking design combines 135° point angle tip for precision, diameter tolerance to h8 grade for excellent concentricity, and precision ground twist body for longer life and rapid drilling.

NEW

FEATURES & BENEFITS

PRECISION

135° point angle - enables self centering & eliminates walking

- ABILITY TO BE RESHARPENED Bit tip can be resharpened to restore profile and sharpness
- LONGER LIFE & RAPID DRILLING
 Precision ground twist better debris removal longer life & rapid drilling
- **CONCENTRICITY** Diameter tolerance to h8 grade – concentricity – Accurate hole diameter

The new HSS-G DIN 338 Jobber Metal Drill Bits deliver rapid drilling, long life & excellent concentricity through precision ground twist drill from solid stock right hand cutting, Type N flute with 135° point angle and diameter tolerance to h8 grade.



GUARANTEED TOUGH.