



Knauf Acoustical Sealant

Knauf Acoustical Sealant is white colored, acrylic based sealant which improves sound insulation and acoustical performance when applied in drywall partitions as per Knauf recommendation. It can be used as a general purpose sealant for compatible joints involving gypsum board, metal, concrete, cement, wood plastics. The most common application is sealing the space between the surface and Knauf UW metal tracks in all types of drywall partitions. It can be used with both Knauf EN- BS and ASTM drywall systems.



Sound Insulation



Moisture Resistant



Mold Resistant

Approx. 280 ml

Material code: 461752



Knauf Acoustical Sealant

Material, Fields of Application, Properties

APPLICATION INSTRUCTIONS

Application surfaces should be clean , dry and free from all contaminants like dust, rust, grease etc. Cut the nozzle at angle and apply the sealant with a hand or air operated cartridge gun tool immediately to spread the sealant over the surface and give a smooth finish. please refer to the datasheet for further details.

PAINTABILITY

A minimum of 2 hours dry time is required before painting with latex or oil base paint . Allow extra t dry time during periods of high humidity and / or above

CLEAN UP

Excess Caulk should be cleaned off, tools and nonporous surfaces while it is in the uncured state using a wet cloth

CAUTION

Direct contact of uncured sealant irritates eye and may irritate skin. Over exposure to vapor may irritate eyes, nose and throat. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands. In case of eye contact, flush eyes with water for 15 minutes. Obtain medical attention. In case of skin contact, remove from skin and flush with water. Keep out of reach of children.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

The information on this datasheet is subject to change without prior notice.

Knauf Head Office

▶ Phone: +971 4 337 7170

▶ Fax: +971 4 334 9659

▶ P.O.Box: 112871, Dubai

▶ info@knauf.ae

www.knauf.ae

Knauf Qatar Branch

P.O.Box 27111
Doha, State of Qatar
Tel: +974 4452 8191
Fax: +974 4452 8181

Knauf RAK Branch

P.O.Box 50006
Ras Al Khaimah, UAE
Tel: +971 7 221 5300
Fax: +971 7 221 5301

