





## Knauf EASY - Finish

### Stucco Surface Finish

Knauf EASY - Finish is a pre mixed gypsum based, white finish compound designed for use as a skimming compound on most interior construction surfaces such as gypsum boards, sand/cement render & cement fibre boards. EASY - Finish is designed for internal use only and is intended to provide a perfectly smooth and level surface ready for the final decoration or wall finishing.

#### **Knauf EASY - Finish**

Material, Fields of Appllication, Properties

# KNAUF

#### **Properties**

- High Quality Filler and Primer Surfacer
- Two in One Primerless Gypsum Board Application
- Low Paint Absorption
- Excellent Surface Coverage
- Easy Application and Smoothening
- Manual, Roller and Spray Application

#### Description

Knauf EASY - Finish is a pre mixed gypsum based, white finish compound designed for use as a skimming compound on most interior construction surfaces such as gypsum boards, sand/cement render & cement fibre boards.

EASY - Finish is designed for internal use only and is intended to provide a perfectly smooth and level surface ready for the final decoration or wall finishing.

#### **Shelf Life**

Knauf EASY - Finish has a shelf life of approximately 6 months from the production date when stored correctly.

#### **Application Fields**

- Gypsum Boards
- Sand / Cement Render
- Cement Fibre Boards
- Pre Cast Concrete

#### Storage

Knauf EASY - Finish should be stored in a dry and covered area out of direct sunlight. When stacking in pallet loads never should you stack more than 2 pallets high. Once the bucket is opened and only partially used it can be re-sealed for any future use.

#### **Order Information**

- 28 Kg (18 Lts.)
- Material no: 528962

#### **Application Method**

- Hand Applied / Spray Applied
- 1st Coat at approximate 1-2 mm thick
- 2nd Coat (if required) 1-2 mm thick. depending on the backgroud surface condition

Note:	

Please contact our sales department for inquiries about storage and packing.

	Knauf Head Office
Þ	Phone: +971 4 337 7170
Þ	Fax: +971 4 334 9659
Þ	P.O.Box: 112871, Dubai
Þ	info@knauf.ae

#### **Knauf Qatar Branch**

P.O.Box 27111 Doha, State of Qatar Tel: +974 4452 8191 Fax: +974 4452 8181

#### **Knauf Manufacturing Plant**

P.O.Box 50006 Ras Al Khaimah, U.A.E. Tel: +971 7 221 5300 Fax: +971 7 221 5301



The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of tis employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefullness of any failure in installation or constructing any structure installation or building or caused by using this leaflet. Readers are adviced to independently verify this information prior to rely on it. In particular, readers must obtain appropriate independent advice on the use of products in specific structures, insllations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification without notice.

www. **KNAUF**.ae

The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.