



Technical Datasheet

10 - 2016

## Knauf Putty Pads

Knauf (FR) Putty Pads are an easy to apply fire and sound rated sealant supplied as a non-setting putty. The pad is hand workable, re-useable and re-serviceable due to its non-setting properties.

## Product Description

Knauf (FR) Putty Pads are an easy to apply fire and sound rated sealant supplied as a non-setting putty. The pad is hand workable, re-useable and re-serviceable due to its non-setting properties.

When electrical sockets and switches are installed in dry lining partitions, the original fire rating of the partition is compromised.

Fitting Knauf (FR) Putty Pads will reinstate the fire rating of the partition for up to two hours (depending on the partition fire rating) and prevent the passage of smoke and flames in a fire, and sound and air movement during service life, through the electrical socket, into the cavity.

Knauf FR Putty Pads are shaped for use on both single double electrical sockets installations in dry lining walls. The pads are supplied in a cross shape for internal installation in a socket.

## Fields of Application

All surfaces must be clean and sound, free from dirt, grease and other contamination. Then remove the backing paper from one side of the pad and for:

Internal Fixing: insert the pad into the socket back box so that the pad completely covers the back and sides. Make a slit to allow the wires to pass through the pad.

Knauf FR Putty Pads are suitable for sealing:

- Single Socket Internal (Rectangle) 170 x 170mm
- Double/Single Internal (Cross Shape) 230 x 170mm

## Properties

- Can be used for all drylining applications
- Ready to use
- No special tools for application Solvent free (no VOC)
- Halogen Free
- Compatible with most building materials
- Non setting
- Non slumping
- Unaffected by moisture
- Reserviceable
- 120 minutes fire resistance in 100mm and 130mm dry lining. EN 1366-3:2004
- Low pressure intumescence
- Cold smoke seal
- Sound insulating BS EN ISO 140-3:1995

## Technical Data

Slump ISO 7390	mm	<0
Density	g/ml	1,6
Skin Forming Time 23°C /55%RH	min	N/A
Temperature Resistance	°C	-70 to 120
Shrinkage	%	None
Application Temperature	°C	+40 to 40

### Sound Insulation:

Knauf FR Putty Pads have been tested according to BS EN ISO 140-3:1995.

Usage of any backing material is optional, due to the tests being conducted with Knauf FR Putty Pads only.

Result: 67 (-2;-7)Rw (C;Ctr) (dB)  
Calculated to BS EN ISO 717-1:1997

### Fire Classification:

Knauf FR Putty pads has been tested in accordance with EN1366-3:2004.

Up to 120 minutes fire resistance in 100mm and 130mm gypsum boards dry walls.

### Limitations:

Knauf FR Putty Pads are not recommended for application on bituminous surfaces or substrates that can exude oils, plasticizers or solvents. Knauf FR Putty Pads are not recommended for underwater applications.

Store between +5°C and +25°C in cool dry conditions.

### Usage:

Knauf FR Putty Pads are supplied ready to fit in boxes of 20.  
One pad required per socket box.

Please contact our sales department for inquiries about storage and packing.

### Knauf Head Office

- ▶ Phone: +971 4 337 7170
- ▶ Fax: +971 4 334 9659
- ▶ P.O.Box: 112871, Dubai
- ▶ info@knauf.ae

### Knauf Qatar Branch

P.O.Box 27111  
Doha, State of Qatar  
Tel: +974 4452 8191  
Fax: +974 4452 8181

### Knauf Manufacturing Plant

P.O.Box 50006  
Ras Al Khaimah, U.A.E.  
Tel: +971 7 221 5300  
Fax: +971 7 221 5301

### Knauf Gypsum India Pvt.Ltd

No. 8 - C, 8th Floor Commercial Complex  
Doshi Tower, New No. 205, (Old No. 156),  
Poonamallee High Road, Kilpauk  
Chennai - 600010.Tamil Nadu, INDIA.  
Tel: +91 44 49580000 | Fax: +91 44 49575300

The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of its employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefulness of any failure in installation or constructing any structure installation or building or caused by using this leaflet. Readers are advised to independently verify this information prior to rely on it. In particular, readers must obtain appropriate independent advice on the use of products in specific structures, insulations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification without notice.

**The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.**