



# MARMORINO

## General Description:

MARMORINO is based on 12<sup>th</sup> century technique, used by the Venetian's to incorporate art into building design. It has been developed from mineral lime, marble dust, natural pigment plus additives and modernized to suite today's design without losing the quality of the traditional product. Although today's designs can dictate colour and texture, the basic formula have been retained to create a spectrum of colour ranging from a natural stone to a mardigras.

## Major Uses:

Can be applied to walls, ceilings, columns, and other curved surfaces, leaving a joint free finish.

Lightweight surface, maximum 3mm thick enable architects to make considerable cost savings on basic construction costs. Each finish is individually designed to suit the tastes and requirements of the designers.

### Classic:

Plain coloured, very smooth with a good sheet. The material is a fine marble dust that is applied in a paste form, can be applied up to 4 layers. The maximum application is 2.5 – 3.0 kg/m<sup>2</sup> based on 2 coats.

### Travertine Effect:

Uses larger marble aggregate and is therefore much tougher. Can be blended with various pigments to create almost any colour. It provides a finish with a porous, line effect that recalls the typical look of Travertine marble. The product is generally applied at the rate of 2.5 – 3.0 kg/m<sup>2</sup> on 2 coats.

### Metallic

Metallic finishes can be achieved by using metallic pigments to be mixed with MARMORINO.

## Support:

- ❖ MARMORINO Decorative plaster can be applied to most solid surface.
- ❖ Dry lined surfaces (plasterboard) should be double boarded with staggered joints.
- ❖ Joints in MDF surfaces should be taped.
- ❖ Raw substrates such as concrete block work, brickwork and similar backgrounds must be rendered with a base plaster to achieve a true, flat surface that is straight both horizontally and vertically.
- ❖ All supports should be sound, clean, dry and free of dust and greasy matter. In hot

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)



**D-111/2004**

weather the support should be moistened. Please note that all substrates should be prepared as if for final decoration.

## Characteristics and Physical Properties:

Colour	See Product Catalogues or any choice of color.
Viscosity	5000 – 9000 cP@25 <sup>0</sup> C
Appearance	Paste
Fire Rating	0 (Not Flammable/Non – Combustible)
Specific Gravity	1.5 to 1.6 kg./lit.
Solid Content	72 - 74
Aggregate Size	0.1 to 1.0mm
<b>Coverage Rate: -</b>	
Theoretical	1.2 – 1.5 kg/m <sup>2</sup> on plaster
Spreading rate	1.0 – 1.2 kg/m <sup>2</sup> on smooth surface or plaster board
Dilution	Water
<b>Drying Time @25<sup>0</sup>C</b>	
Touch Dry	3 hrs.
Sandability	4 – 6 hrs.
Recoatibility	12 hrs.
Binder	Vinyl Versatic

## Application:

- ❖ All surfaces are treated with a tie – coat (MAS ACRITEX PRIMER) to ensure good adhesion of the product to the background surface.
- ❖ The finishes are mixed on with water and then applied in a number of thin layers to build a thickness of 2 – 3 mm.
- ❖ When dry, colour washing may be necessary for some of the finishes.
- ❖ This surface, after curing, are oiled and / or waxed according to the architects specification.
- ❖ For use in bathrooms or kitchen the surface can treated with water proofing sealer.

## Waxing:

Application of wax is recommended as the last step for MARMORINO. Wax due to its penetration and good spreading over the surface of MARMORINO gives excellent protection from moisture, dust and enhances the color, design and gives an extra shine on the surface.

## Packaging:

Available in 25 kg buckets



## Shelf Life:

MARMORINO Decorative plaster can be stored for up to 12 months in unopened packaging. Under good conditions away from direct sunlight and rainfall.

## Health and Safety:

As with all chemical products, caution should always be exercised. MARMORINO take all necessary precautions to ensure employee welfare and to comply to Health and Safety regulation.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

FACTORY	:	P.O. BOX NO: 23085,SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5311777, FAX 06 - 5311330:	 
SHOWROOM	:	P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5328533, FAX 06 - 5328610	
Website	:	<a href="http://www.maspaints.com/">http://www.maspaints.com/</a> Email : masuae@emirates.net.ae	<b>D-111/2004</b>