Hazardous Location

- · Switches, cords and motors are sealed to prevent sparking and accidental explosion in highly-combustible areas
- Durable one-piece molded plastic polyethylene housing. Unit & water supply are both portable
- 48" unit with one horsepower motor delivers 17,500 CFM's. 36" unit with 1/2 horsepower motor delivers 9,600 CFM's.
- Operate for pennies a day, a fraction of the cost of standard air-conditioning
- Environmentally friendly with efficient / effective resource use
- Cooling is accomplished naturally through the process of evaporation without the use of harmful refrigerants
- Long-term dependability plus almost maintenance-free operation

36"

36" HAZMAT UNIT SPECIFICATIONS

9,600 Air Delivery CFM Fan motor 1/2 h.p. / 110/220v / 9.2 amps Pump 1/4 h.p. / 110/220v / 4.2 amps Water reservoir 32 gallons Dimensions 67"h x 62"w x 32"d Unit weight 270 lbs. Shipping weight 310 lbs. 68"h x 64"w x 33"d Box Size Cooling Capacity 2,500 sq. ft.

Stock # PAC2K36HZ



48"

48" HAZMAT UNIT SPECIFICATIONS

Air Delivery CFM 20,000 1 h.p. / 110/220v / 13.8 amps Fan motor 1/4 h.p./ 110/220v / 4.2 amps Pump Water reservoir 25 gallons Dimensions 86"h x 74"w x 36"d Unit weight 400 lbs. Shipping weight 460 lbs. Box Size 88"h x 75"w x 38"d Cooling Capacity 4,000 sq. ft.

Stock # PAC2K48HZ



Tel: +971 4 88 66 520 , Fax: +971 4 88 66 521 , Email: info@constromech.com