

## ة سيسة الفج al fajer establishment A MEMBER OF AL FAJER GROUP



## San Marco Paints Collection!

## **IDROFIS**

#### **PRIMER**

series 470



0006 transparent

## Water-based acrylic wall fixative

styrene-acrylic copolymer in water Based on emulsion, suitable for impregnating the wall surface, in indoor and outdoor use. Good penetrating and consolidating power.

Indicative spreading rate: 50-60m<sup>2</sup> /I per coat Number of coats: 1

Tools: brush, roller and spray gun Dilution: 6 or 8 parts or water per one of fixative

Pack.: 15 I, 5 I, 1 I

## **WALL STUCCO**

## **THIN STUCCO**





0019 white

## Stucco paste for interior thin levelling

It is a vinyl copolymer based aqueous emulsion that is ideal for the direct levelling of interior surfaces, new or old, such as plaster coat, concrete and wood. Ready-to-use and simple to apply. The product is applied in thin overlying layers. With its creany consistency, easy and flowing application, WALL STUCCO allows you to obtain large homogeneous surfaces with low consumption of the product. Also indicated for levelling moderate cracks and depressions.

Indicative spreading rate: 4-6 m<sup>2</sup>/kg per coat Tools: putty knife or trowel

Dilution: ready to be used Number of coats: 1 - 2

Pack. : 20 kg

## **TAMSTUCCO PASTA**

series 940



0006 white paste

## THICK STUCCO

#### **Wood and wall putty in paste**

Based on vinyl polymer in water emusion, to be used indoors for smoothing coats and to level out imperfections, cracks and gaps on both wood, wall and plasterboard

Indicative spreading rate: with an applied thickness of 500-600 microns a spreading rate of 1m<sup>2</sup>/kg is obtained Tools: skreper or trowel

Dilution: ready to be used

Pack.: 20 kg, 5 kg, 1 kg, 0.50 kg













## **BRAVOCASA**

series 408



0019 white

# Highly washable water-based paint for outdoor and indoor use

**HIGH OUALITY ACRYLIC PAINT** 

Based on vinyl-versatic binder in water emulsion, for all-purpose outdoor and indoor use. High coverage and strong capacity to mask Imperfections in the support surface. Easy to apply, anti-drip and good spreading.

Indicative spreading rate: 9-12m<sup>2</sup> /I per coat Number of coats: 2

Tools: brush, roller, spray and airless gun Dilution: with water

by brush base coat at 35-40% second coat at 30-35% by roller at 25%

Pack.: 14 I, 4 I, 0.75 I

## **LAGUNA**

series 370



0019 white

#### **ACRYLIC PAINT**

# Breathable water repellent acrylic water-based paint for indoor and outdoor use

Based on polymeric binder in aqueous dispersion, suitable for indoor surfaces, including those subject to moisture such as bathrooms and kitchens. Resistant to alkalis and good resistance to abrasion. High coverage and breathability. Excellent whiteness. Easy to apply, even, matt appearance.

Indicative spreading  $\mbox{ rate: 8-10m}^2\mbox{ /I per coat}$ 

Number of coats: 2

Tools: brush, roller, spray and airless gun

Dilution: with water

base coat at 40-45%; second coat at 30%

Pack: 15 I, 4 I, 0.75 I

## **COMBAT 999 EW**

series 489



Resistant to mould accsording to UNI 9805:1991 norm

## **MOULD RESISTANT EMULSION**

# Breathable hygienic water-based paint mould inhibiting for interior use - high whiteness

A vinyl versatate binder based paint highly suited for interior rooms exposed to a high level of air-borne moisture and inclined to the formation of moulds. It is used to create exceptionally white, flat and uniform finishes. Thanks to its hygienic strength, this product maintains the original appearance of the surfaces for a long period of time and improves the level of comfort in the room. It also provides excellent coverage, high breathability as well as good drip resistance, brushability and flow.

#### Note

We suggest COMBAT 999 as anti mould super washable acrylic emulsion paint, it has very white hiding power for walls and ceiling surfaces.

Indicative spreading rate: 9-12m² /I per coat

Number of coats: 2

Tools: brush, roller, spray gun and airless Dilution: with water

first coat at 50% subequent coats at 30-40%

Pack.: 14 I, 5 I

## **ALBUS**

#### ANTI DRIP PAINT FOR CEILING

#### series 484



0019 white

# Breathable, anti-drip water-based interior paint

Based on high coverage vinyl resin in aqueous dispersion. Used to create exceptionally white, flat and uniform finishes. Easy to apply with good drip resistance.

#### Note:

Very white hiding power we suggest ALBUS, for ceiling this is a very good solution.

Indicative spreading rate: 9-12 m²/I per coat Number of coats: 2

Tools: brush, roller, spray and airless gun

Dilution: with water

base coat at 50% with water second coat at 30-40%

Pack.: 14 I, 5 I







