



MAS STUCCO

General Description:

MAS STUCCO is water – based putty, based on emulsion resins; special oils and selected fillers to provide a marble like finish effect. The glossy appearance and shade of differences obtain gives unique and a great value of decoration for interior. It contains anti fungal and anti bacterial additives.

Advantages and Uses:

- Wall decorative coating for interior plasters and gypsum.
- Water soluble material and environmentally safe.
- Smooth to touch, odourless, non – toxic and extremely pleasing in appearance.

Characteristics and Physical Properties:

Colour	See Product Catalogues or any choice of color.
Viscosity	Paste
Appearance	Glossy with Matt shade.
Specific Gravity	1.7 +/- 0.1 kg./lit.
Average Coat	2 or More.
Theoretical	1.0 – 1.5 kg/m ² on plaster
Spreading rate	0.5 – 0.8 kg/m ² on smooth surface or plaster board
Solvent	Water
Drying Time @25°C	
Touch Dry	3 hrs.
Sandability and coatability	4 – 6 hrs.
Air Temperature	+5°C min. +35°C max.
Relative Humidity of the air	<60%
Surface Temperature	+5°C min. +35°C max.

Application Procedure:

- Prime the substrate with mas masonry primer or primart on very absorbent and chalky surfaces.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- Smooth the surface by stainless steel spatula using marble stucco to get a uniform finish.
- After 6 hours from the last coat, sand with sand paper in order to smooth the surface and take off surface defects.
- Apply the last coat of marble stucco by stainless steel spatula thoroughly. To obtain a different effect, choose a different size of spatula, and apply artistically.
- After 5 – 10 minutes press the spatula and move it on the surface to obtain more glossy effects.
- To enhance the level of gloss and to obtain water repellancy, one coat o special wax can be applied though it is not highly recommended on the treated surface since they tend to impair the characteristics which give the product its prestige.

Storage:

Shelf life 12 months minimum if stored below 25°C.

Cleaning of Tools:

All tools should be cleaned with Water as soon as possible.


Packing:

Available in 5 Kgs. and 20 Kgs.

Physiological Hazards:

MAS STUCCO does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS STUCCO is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY	:	P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	http://www.maspaints.com/ Email : masuae@emirates.net.ae



D-111/2004