PERFORMANCE CEILINGS



More scope for innovation

THERMATEX Plain



THERMATEX ceiling tiles are made of modern, bio-soluble mineral wool, perlite, clay and starch with excellent outstanding physical properties in fire resistance and acoustic performance.

SYSTEM Exposed Grid System, demountable ceiling

Free span system, with exposed or concealed suspension

Bandraster system, with exposed or concealed suspension

A Concealed system, panels demountable / non demountable


Dimensions 600 x 600 mm, 625 x 625 mm,

plank sizes available on request

Thickness / Weight 15 mm (c. 4.5 kg/m²) 19 mm (c. 5.7 kg/m²)

Colour White similar to RAL 9010

Edge details SK, VT 15/24, AW, GN



TECHNICAL PERFORMANCE

Reaction to fire A2-s1, d0 as per EN 13501-1

Fire protection Up to 60 minutes as per BS 476: parts 20 - 23 (according to test certificate)

Sound absorption EN ISO 354

 $\alpha_{\rm W}$ = 0.10(L) as per EN ISO 11654 NRC = 0.10 as per ASTM C 423


Sound attenuation D_{n,c,w} = 34 dB as per EN 20140-9 (15 mm thickness, according to test certificate)

Light reflectance Up to 92%

Thermal conductivity $\lambda = 0.052 - 0.057 \text{ W/mK}$ as per DIN 52612

Humidity Up to 95% RH

Clean room classification ISO - Class 4 (as per ISO 14644-1)









Knauf AMF GmbH & Co. KG
Elsenthal 15
D-94481 Grafenau , Germany
Phone +49 (0) 8552 / 422-0 - Fax +49 (0) 8552 / 422-32
info@knaufamf.de - www.amfceilings.com

Due to reproduction processes colours shown in this catalogue may differ from the actual product colour. Product selection should always be made from AMF samples. All details and technical information stated in this brochure or other publicity material referring to AMF ceiling systems are based on test reports obtained under laboratory conditions. It is the responsibility of the customer to ensure that this data is suitable for the proposed application.

All information provided is based on current technical data. Further relevant test reports, assessments and installation guidelines are available. All system details conform with current standards and are based on the use of AMF products and system components. AMF accepts no liability or responsibility for use of third party components, or for any variations to conditions stipulated in test data. Mixing of production batches is not recommended.

All technical data is subject to change without prior notice and is governed by AMF Terms and Conditions of Sales. This catalogue supersedes all previous editions. Errors and omissions excepted. Printing errors excepted.

MADE IN GERMANY 04/2012